



Europäisches Patentamt
European Patent Office
Office européen des brevets



Publication number: **0 509 636 A1**

EUROPEAN PATENT APPLICATION

Application number: **92302069.7**

Int. Cl.⁵: **H01P 1/203**

Date of filing: **11.03.92**

Priority: **19.04.91 US 688038**

Date of publication of application:
21.10.92 Bulletin 92/43

Designated Contracting States:
DE FR GB IT

Applicant: **SPACE SYSTEMS / LORAL INC.**
3825 Fabian Way
Palo Alto, California 94303-4697(US)

Inventor: **Fiedziuszko, Slawomir J.**
C/O Space Systems/Loral, Inc. 3825 Fabian
Way
Palo Alto, CA 94303-4697(US)
Inventor: **Curtis, John A.**
C/O Space Systems/Loral, Inc. 3825 Fabian
Way
Palo Alto, CA 94303-4697(US)


Representative: **Crawford, Andrew Birkby et al**
A.A. THORNTON & CO. Northumberland
House 303-306 High Holborn
London WC1V 7LE(GB)

Miniature dual mode planar filters.

A dual mode microstrip resonator (1) usable in the design of microwave communication filters. The substantially square resonator (1) provides paths for a pair of orthogonal signals which are coupled together using a perturbation located in at least one corner of the resonator (1). The perturbation can be introduced by notching (3) the resonator (1) or by adding a metallic or dielectric a stub (83) to the resonator (1).

FIG 2

(a)



EP 0 509 636 A1

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates to high frequency electronic circuits, and more particularly to microwave communication filters implemented using planar transmission line fabrication techniques.

2. Description of Background Art

Design techniques for single mode planar microwave filters, such as broadside edge coupled filters, have long been established. Implementation of planar microwave filters is often achieved using microstrip and stripline fabrication techniques. Microstrip is formed by etching a circuit pattern on one side of two metal layers separated by a dielectric substrate. The unetched side serves as a ground plane. Stripline circuits are fabricated by etching a metal layer sandwiched between two dielectric layers having outer surfaces coated by metal ground planes. These single mode planar filters, however, are of limited utility for most high performance microwave applications due to their typically high insertion loss and their impracticality for filter passbands of less than 5%. The high performance requirements for communication satellite frequency multiplexers typically require the use of dual mode cavity or dielectric resonator filters to realize self equalized, quasi-elliptic responses having pass bands often less than 1%. These filters have the drawbacks of relatively large size and high cost.

In U.S. patent no. 3,796,970 by Snell, an orthogonal resonant filter was disclosed in which the two surface dimensions are each designed to be one-half the wavelength of a desired frequency. Figure 1 shows the resonator 4 of Snell having a rectangular shape with side lengths of l_1 and l_2 . Signal conductors 4 are used to couple signals to and from resonator 2. Accordingly, the element supports two resonant orthogonal standing waves, and external coupling to each wave can be provided independently.

In Soviet Union patent no. 1,062,809, a rectangular resonator is shown with inputs and outputs electromagnetically coupled to the resonator.

In Japanese patent no. 58-99002, an adjustable notch in a slot line ring is disclosed for tuning the center frequency and bandwidth of a microwave filter.

SUMMARY OF THE INVENTION

In accordance with the present invention, a dual mode microstrip resonator (1) is used in the design of high performance microwave commu-

nication circuits. A perturbation is added to dual mode resonator (2) of the prior art (shown in FIG. 1) at a point that lies on an axis of symmetry (17) formed by the bisection of characteristic vectors (6,8). Vectors (6,8) represent orthogonal dual modes which characterize the resonator (2) of the prior art. This perturbation added to resonator (1) facilitates coupling between the two orthogonal modes within resonator (1). By coupling the orthogonal modes in the manner of the present invention, each resonator (1) can be used to realize a second order transfer functions (having two frequency poles). Combining multiple resonators (1) enables the efficient realization of higher order filter circuits.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a top view of a prior art microstrip type planar transmission line illustrating a dual mode resonator 2;

FIG. 2(a) is a top view of a dual mode microstrip type resonator 1 comprising notch 3;

FIG. 2(b) is a top view of a dual mode microstrip type resonator 9 comprising stub 5;

FIG. 2(c) is a top view of a dual mode microstrip type resonator 11 comprising hole 7;

FIG. 3 is a top view of a dual mode microstrip type filter 45 comprising resonator 35 of the present invention and coupling transmission lines 37, 39, 41 and 43;

FIG. 4 is a relief view of a fourth order filter utilizing dual mode resonators 20, 22 of the present invention;

FIG. 5 is a top view of an eighth order filter utilizing dual mode resonators 63 of the present invention; and

FIG. 6 is a top view of an eighth order filter utilizing dual mode resonators 77 of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to FIG. 2(a), a dual mode microstrip resonator 1 of the present invention is shown. In the preferred embodiment, resonator 1 is substantially square in shape, having side lengths l_3 and l_4 which are equal to the half wave lengths of the orthogonal resonant signals represented by characteristic vectors 13 and 15 respectively. Vectors 13 and 15 are bisected by axis of symmetry 6. Coupling notch 3 lies perpendicular to axis of symmetry 6 in such a manner that axis 6 bisects the notch 3. Coupling notch 3 causes each of the resonant signals represented by vectors 13 and 16 to symmetrically reflect and couple with the corresponding signal in the orthogonal direction.

Since the purpose of the notch 3 is to distort or perturb the resonant signals, any placement of the notch 3 which distorts the signal will effect coupling of the orthogonal signals. Characteristic vectors 13, 15 can be drawn in any orientation such that they are parallel to the edges of the resonator, and the notch 3 can be placed accordingly with respect to a bisecting axis of symmetry 6, as described above. It is also possible to effect coupling by using multiple notches 3 or perturbations located in various corners of resonator 1. The variability of notch orientation is demonstrated in FIG. 5 where notches 67 alternate. In FIG. 6, three of the resonators 77 have three notches 79 which are oriented to the interior of the circuit while a fourth is randomly oriented outward.

Use of a substantially square resonator 1 provides an advantage over narrow single mode resonant filters by providing higher Q, since the losses are reduced by the wide geometrical dimensions available in the direction of resonance. These Q factors are significantly improved when superconductive materials are used in constructing the circuitry. Also, the use of substantially square resonators, facilitates the realization of dual mode designs and elliptic functions and self equalized planar filter designs.

Referring now to FIG. 2(b), a resonator 9 of the present invention is shown with a stub 5 perturbation. This stub 5 operates as an alternative to notch 3 in FIG. 2(a), to couple together the two independent orthogonal modes traversing resonator 9. This stub 5 can be constructed in any symmetrical shape and of any material which perturbs the electromagnetic fields resident on resonator 9. The stub 5 can be formed by depositing a metallic or dielectric material on the surface of resonator 9. The shape of stub 5 is not critical except that the geometry should produce a symmetrical signal reflection (half on each side) relative to axis of symmetry 19.

FIG. 2(c) shows a resonator 11 which uses a hole 7 as a coupling means instead of stub 5. As in stub 5 of FIG. 2(b), the hole should produce a symmetrical signal reflection relative to axis of symmetry 21. Input conductor leads 37 and 39 are used to provide electromagnetic signals to resonator 35. The inputs 37, 39 and outputs 41, 43 are capacitively coupled to resonator 35 through gaps C1-C4 respectively. The signal entering resonator 35 from input 37 introduces an electromagnetic signal which resonates along characteristic vector 31. Input conductor lead 39 introduces a signal which resonates along characteristic vector 33 orthogonal to vector 31. Notch 47 causes each of the resonant signals represented by vectors 31 and 33 to symmetrically reflect and couple with the corresponding signal in the orthogonal direction. Cou-

pling between the inputs 37, 38 and resonator 47 is arranged so that the input 37, 38 strips are centered with respect to the edge of the resonator 47. Although this configuration provides coupling at a point of maximum resonant signal strength, alternate coupling schemes are well known in the art as disclosed by U.S. Patent No. 3,796,970. Output 41 and output 43 are used to deliver coupled signal components from resonator 35.

Referring now to FIG. 4, a relief view of a fourth order filter utilizing dual mode resonators 20, 22 of the present invention is shown. The circuit structure is fabricated by constructing dielectric substrate 30 over conductive ground plane 28. Various circuit components 16, 20, 24, 22, 18 are then deposited or etched using microstrip or strip line planar fabrication techniques. In the fourth order filter of FIG. 4, conductor lead 29 provides an input signal to resonator 25. The dual pole generation of resonator 25 is effected through the notch 24 coupling of orthogonal signal components. The second order signal is then transmitted along conductor lead 31 to the second resonator element 27 where additional second order filtering is introduced. The output signal of this fourth order circuit is sampled along output 33.

Referring now to FIG. 5, an eighth order filter using four dual mode resonators 63 of the present invention is shown. The input signal is continuously sampled at input 61, filtered through resonator elements 63, and coupled by conductor leads 65. The eighth order output of this filter structure is sampled by output 69.

Referring now to FIG. 6, an alternative embodiment of an eighth order filter using dual mode resonators 77 of the present invention is shown. The input signal to this circuit is provided through input 71. Resonators 77 each provide a second order (two pole) effect through coupling of two orthogonal components facilitated by notches 78. The individual resonator elements 77 are coupled together by conductor leads 75, and the circuit is sampled at output 73.

The invention has now been explained with reference to specific embodiments. Other embodiments will be apparent to those of ordinary skill in the art in light of this disclosure. Therefore, it is not intended that this invention be limited, except as indicated by the appended claims.

Claims

1. A dual mode planar filter comprising:
substantially square resonating means having a pair of orthogonal resonating paths for conducting two modes of electromagnetic signals and having a perturbation means located in at least one corner of the resonating means

for coupling the electromagnetic signals between the two modes;

at least one signal input electromagnetically coupled to the resonating means for delivering electromagnetic signals to the resonating means such that the signals propagate along the resonating paths; and

at least one signal output electrically coupled to the resonating means for delivering coupled electromagnetic signals from the resonating means.

2. The planar filter as in claim 1 wherein the resonating means is implemented using microstrip.
3. The planar filter as in claim 1 wherein the resonating means is implemented using stripline.
4. The filter as in claim 3 wherein the microstrip is a superconductor.
5. The filter as in claim 4 wherein the strip line is a superconductor.
6. The planar filter as in claim 1 wherein the perturbation means comprises at least one notch for disturbing orthogonal electromagnetic signals, resulting in the coupling of electromagnetic signals.
7. The planar filter as in claim 1 wherein the perturbation means comprises a metallic stub for disturbing orthogonal electromagnetic signals, resulting in the coupling of the electromagnetic signals.
8. The planar filter as in claim 1 wherein the perturbation means comprises of a dielectric stub for disturbing orthogonal electromagnetic signals, resulting in the coupling of the electromagnetic signals.
9. The planar filter of claim 1 wherein the signal inputs and outputs are electromagnetically coupled to the resonating means by a capacitive gap.

50

55

FIG. 1
PRIOR ART






FIG 2

(a)



(b)



(c)




Fig. 3




FIG. 4




FIG. 5





FIG. 6





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

DOCUMENTS CONSIDERED TO BE RELEVANT			EP 92302069.7
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. CL.5)
X	<u>US - A - 4 488 131</u> (GRIFFIN) * Column 1, lines 17-29; fig. 1; column 1, line 59 - column 2, line 21 *	1,2,3, 6,8,9	H 01 P 1/203
D,Y	-- <u>US - A - 3 796 970</u> (SNELL) * Fig. 1-6; claims *	1,2,3, 6,9	
Y	-- <u>US - A - 3 560 887</u> (NAPOLI) * Fig.; claims *	1,2,3, 6,9	
A	-- <u>US - A - 4 352 076</u> (SAITHO) * Fig. 7; column 4, lines 10-20 *	1,2,3, 7,9	
			TECHNICAL FIELDS SEARCHED (Int. CL.5)
			H 01 P H 03 H
The present search report has been drawn up for all claims			
Place of search VIENNA		Date of completion of the search 22-07-1992	Examiner HEINICH
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ----- & : member of the same patent family, corresponding document	

EPO FORM 1503 03.92 (P0401)




FIG. 1
PRIOR ART






FIG 2

(a)



(b)



(c)




Fig. 3




FIG. 4




FIG. 5




FIG. 6

